

电梯随行电缆-低提升高度

Flat Traveling Cable for Low Rise Elevator

60227 IEC71f (TVVB)

产品标准 (Product Standard): GB/T 5023.6/IEC 60227-6

型号 Type	规格mm ² Specification	导体结构 Conductor Structure	成品最大直径 Diameter.(mm)	额定电压 +U ₀ /U(V)	20°C时导体直流电阻 20°C conductor DCR (Ω/KM)
60227 IEC71f(TVVB)	3×0.75	30/0.18	4.75×8.2	300/500	≤26
60227 IEC71f(TVVB)	3×1.0	40/0.18	4.95×11.5	300/500	≤19.5
60227 IEC71f(TVVB)	6×0.75	30/0.18	4.75×18	300/500	≤26
60227 IEC71f(TVVB)	6×1.0	40/0.18	4.95×19.2	300/500	≤19.5
60227 IEC71f(TVVB)	9×0.75	30/0.18	4.75×25	300/500	≤26
60227 IEC71f(TVVB)	9×1.0	40/0.18	4.95×26.8	300/500	≤19.5
60227 IEC71f(TVVB)	12×0.75	30/0.18	4.75×33.7	300/500	≤26
60227 IEC71f(TVVB)	12×1.0	40/0.18	4.95×36.1	300/500	≤19.5
60227 IEC71f(TVVB)	16×0.75	30/0.18	4.75×44	300/500	≤26
60227 IEC71f(TVVB)	16×1.0	40/0.18	4.95×47.2	300/500	≤19.5
60227 IEC71f(TVVB)	18×0.75	30/0.18	4.75×48.8	300/500	≤26
60227 IEC71f(TVVB)	18×0.75	40/0.18	4.95×52.2	300/500	≤19.5
60227 IEC71f(TVVB)	20×0.75	30/0.18	4.75×53.5	300/500	≤26
60227 IEC71f(TVVB)	20×1.0	40/0.18	4.95×57.5	300/500	≤19.5
60227 IEC71f(TVVB)	24×0.75	30/0.18	4.75×64.5	300/500	≤26
60227 IEC71f(TVVB)	24×1.0	40/0.18	4.95×65.5	300/500	≤19.5
60227 IEC71f(TVVB)	3×1.5	29/0.25	5.6×12.7	450/750	≤13.3
60227 IEC71f(TVVB)	3×2.5	48/0.25	6.25×15	450/750	≤7.98
60227 IEC71f(TVVB)	6×1.5	29/0.25	5.6×24.6	450/750	≤13.3
60227 IEC71f(TVVB)	6×2.5	48/0.25	6.25×27.5	450/750	≤7.98
60227 IEC71f(TVVB)	9×1.5	29/0.25	5.6×30.9	450/750	≤13.3
60227 IEC71f(TVVB)	9×2.5	48/0.25	6.25×39.8	450/750	≤7.98
60227 IEC71f(TVVB)	12×1.5	29/0.25	5.6×41.6	450/750	≤13.3
60227 IEC71f(TVVB)	12×2.5	48/0.25	6.25×50.7	450/750	≤7.98

TVVBP, TVVBPG

产品标准 (Product Standard): JB/T 8734.6

型号 Type	规格mm ² Specification	导体结构 Conductor Structure	成品最大直径 Diameter.(mm)	额定电压 +U ₀ /U(V)	20°C时导体直流电阻 20°C conductor DCR (Ω/KM)
TVVBP(铜网屏蔽)	2×2P×0.75	30/0.18	9.0×15.2	300/500	≤26
TVVBP(铜网屏蔽)	3×2P×0.75	30/0.18	9.0×20.8	300/500	≤26
TVVBP(铜网屏蔽)	16×0.75+2×2P×0.75	30/0.18	9.0×38.8	300/500	≤26
TVVBP(铜网屏蔽)	18×0.75+2×2P×0.75	30/0.18	9.0×37.6	300/500	≤26
TVVBPG-TV(铜网屏蔽)	18×0.75+2×2P×0.75+ 1×0.75+6×0.5+75-5	30/0.18 20/0.18	9.0×46.8	300/500	≤26/39
TVVBP(铜网屏蔽)	24×0.75+2×2P×0.75	30/0.18	9.0×43.4	300/500	≤26
TVVBP(铝箔屏蔽)	16×0.75+2×2P×0.75	30/0.18	9.0×38.8	300/500	≤26
TVVBP(半导体屏蔽)	24×0.75+2×2P×0.75	30/0.18	9.0×43.4	300/500	≤26